



Dress with Bias Tape Ties

Materials required:

- 5/8 yd.–1 1/8 yd. cotton fabric, depending on size
- 3 yd. double fold bias tape
- Coordinating all-purpose thread

Making the Dress

1. Cut a fabric rectangle the width of the fabric and the length indicated.
Finished dress length is measured from the shoulder to the hem.

<u>Size</u>	<u>Size of cut rectangle</u>	<u>Finished dress length</u>
Small (2–4)	19"–25" L x 42" W	16"–22" long
Medium (5–7)	26"–31" L x 42" W	23"–28" long
Large (8–10)	32"–37" L x 42" W	29"–34" long
X-Large (11 and above)	38" L or more x 42" W	more than 35" long

2. Fold fabric in half, meeting selvage edges. Stitch or serge the seam. Press seam open or to one side. Center seam on the stitched tube. (This will be the center back of the dress.)
3. Cut out armholes on upper side edges using the appropriate Armhole Template Pattern on p. 1.
4. Cut two lengths of bias tape long enough to bind the armholes. Bind cut edges of armhole and edgestitch tape.
5. Fold under casings at the front and back top edges (the edges containing the armholes). Fold edge under 1/4", then 3/4" to make each casing. Edgestitch casings.
6. Cut remaining bias tape into two equal pieces. Stitch folds and cut ends of tape together with a narrow zigzag to prevent stitches from breaking. Insert one piece through each of the casings, allowing equal extensions at each end. Machine stitch at center front and center back to prevent tape from pulling out of the casing.
7. Hem the lower edge, turning under 1/4" and then 2". Edgestitch hem.

To wear the dress, pull up tape ties to gather the top of the dress to fit. Tie bias tape at the shoulders.

Optional: Trim dress as desired. Several possibilities are listed on p. 1.

Modifying a Pillowcase to Make the Dress

Materials required:

- One new or gently used cotton pillowcase
- 2 1/2 yd. double fold bias tape
- 12"–18" elastic, 1/4" wide, depending on size
- Coordinating all-purpose thread

Making the Dress

1. Trim off the seamed end of the pillowcase. Do not cut off the hemmed edge; it will be the hem of the dress.
2. Cut out armholes on the cut edge, using the Armhole Template Pattern as a guide.
3. Fold under casings at the front and back top edges (the edges containing the armholes). Fold edge under 1/4", then 1/2" to make each casing. Edgestitch casings.
4. Cut elastic into two equal lengths (6" for size small, 7" for size medium, 8" for size large, 9" for size X-large). Insert one length into each casing. Thread elastic through the casing; stitch elastic ends to the outer edges of the casing to prevent them from pulling out. This gathers the front and back edges.
5. Cut two 38" lengths of double fold bias tape. Open tape and turn under 1/4" on each end to finish the ends of the tape. Refold tape and encase armhole, allowing equal tape extensions at each end of the armhole so the dress can be tied at the shoulders. Edgestitch tape.

Optional: Trim dress as desired. Several possibilities are listed on p. 1.