

# **MATERIAL SAFETY DATA SHEET**

OSHA Hazard Communication Standard 29 CFR 1910.12000

U. S. Department of Labor Occupational Safety and Health Adm. OMB 1218-0072

Identity (used on label): PDSCo Grout (20%)

### **SECTION I**

Manufacturer : PDSCo

P.O. BOX 507,

105 West Sharp Street El Dorado, AR 71730

**Emergency Phone** : (800) 243-7455 **Information Phone** : (870) 863-5707

# SECTION II HAZARDOUS INGREDIENTS

Hazardous Components	OSHA PEL	TLV	Other Limits	%
Crystalline Quartz CAS# 14808-60-7 (naturally occurring contaminant)	-	-	*	2-6%
Respirable Crystalline Quartz			NIOSH	
present (TWA) proposed (TWA)	0.1 mg/m <sup>3</sup> -	0.1 mg/m <sup>3</sup> 50ug/m <sup>3</sup>	50ug/m³ -	<2% -
Nuisance Dust Respirable Total Dust	5 mg/ m <sup>3</sup> 15 mg/ m <sup>3</sup>	5 mg/ m <sup>3</sup> 10 mg/ m <sup>3</sup>	- -	-

<sup>\*</sup> Warning: This product contains a small amount of crystalline silica which may cause delayed respiratory disease if inhaled over a prolonged period of time. Avoid breathing dust. Use NOISH/MSHA approved respirator when TLV for crystalline silica may be exceeded. IARC Monographs on the evaluation of the Carcinogenic Risk of Chemicals to Humans (volume 42, 1987) concludes that there is 'limit evidence' of the carcinogenicity of crystalline silica to humans. IARC classification 2A.

### SECTION III PHYSICAL CHEMICAL CHARACTERISTICS

Boiling Point : N/A
Vapor Pressure (mm Hg at 20°C) : N/A
Vapor Density (Air = 1) : N/A
Solubility in Water : Negligible

**Appearance & Odor** : Pale grey to buff powder or granules, odorless.

Specific Gravity: 2.5Melting Point: N/AEvaporation Rate: N/A

## SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flash Point : N/A
Flammable Limit : N/A
LEL : N/A
UEL : N/A

**Extinguishing Media** : Not Applicable

**Special Fire Fighting Procedure** : Inorganic mineral/non-flammable.

Unusual Fire and Explosion Hazards : N/A

#### REACTIVITY DATA **SECTION V**

Stability Unstable **Stable** X

**Conditions to Avoid** None Known Materials to Avoid None Known

None Known **May Occur Hazardous Polymerization** Will Not Occur X

#### **SECTION VI HEALTH HAZARD DATA**

Routes of Entry Inhalation: Yes Skin: No Ingestion: No

**Health Hazards (Acute-Chronic)** May cause delayed respiratory disease if dust inhaled over a prolonged

period of time.

Carcinogenicity NTP: No IARC: Yes N/A OSHA Req: No

> IARC Monographs on the evaluation of the Carcinogenic Risk of Chemicals to Humans (volume 42, 1987) concludes that there is "limited evidence" of the carcinogenicity of crystalline silica to humans.

Sighs and Symptoms of

**Hazardous Decomposition** 

**Exposure** 

Excessive inhalation of dust may result in shortness of breath and

reduced pulmonary function.

**Conditions Aggravated by** 

**Exposure** 

Individuals with pulmonary and/or respiratory disease including but not limited to asthma and bronchitis be precluded from exposure to dust.

**Emergency First Aid** Eyes: Flush with water.

Gross inhalation of dust: Remove to fresh air. Give oxygen or artificial

respiration if necessary. Get medical attention immediately.

### PRECAUTIONS FOR SALE HANDLING AND USE **SECTION VII**

In Case Released or Spilled Vacuum if possible to avoid generating airborne dust. Avoid breathing

duct. Wear an approved respirator. Avoid adding water, the product will

become slippery when wet.

**Waste Disposal** Consult appropriate Federal, State, and Local regulatory agencies to

ascertain proper disposal procedures.

Caution In Handling and Storing Avoid breathing dust, use NOISH/MSHA approved respirator when TLV

limits for Crystalline Silica may be exceeded.

Other Precautions Slippery when wet.

### SECTION VIII **CONTROL MEASURES**

OSHA standard 1910.134 or ANSI Z88.2-1980 specification. **Respiratory Protection** 

Ventilation Local and mechanical exhaust as appropriate.

**Protective Gloves** Not Required. **Eye Protection** Recommended.

Other Protection Equipment Not required for normal use.

Work/Hygienic Practices Normal personal hygiene required.