









-  I-BEAM BLOCKING
SEE SOIL BEARING CAPACITY CHARTS FOR SPACING
-  COLUMN BLOCKING
SEE SOIL BEARING CAPACITY CHARTS FOR PAD SIZE
-  SHEARWALL BLOCKING
-  SHEARWALL FRAME TIE
-  CENTER LINE TIES
-  VERTICAL TIE
MAX. SPACING 9'-9" CENTER TO CENTER
-  LONGITUDINAL TIES

 SHEARWALL TIE

BLOCKING LEGEND:

- 1) ALL EXTERIOR DOORS, BAY WINDOWS, RECESSED SIDEWALLS AND EXTERIOR WALL OPENINGS 48" OR GREATER. WILL REQUIRE BLOCKING ON EACH SIDE
- 2) 32' WIDE HOMES REQUIRED TO BE BLOCKED
MIN 8'-0" ON CENTER BETWEEN COLUMNS.



TOWNHOMES
VISION - EXPERIENCE - INTEGRITY - BUILDING YOUR FUTURE

TownHomes
P.O. BOX 1059
LAKE CITY, FLORIDA
32056

Date: 10-2-07	Revisions	Cad#: 2828A
Dr'n: ROB		
Parent: NEW		
Code: T (07)		
ZONE 2	Model: 2828-183	Print: BLOCKING PLAN